PRODUCT FAMILY DATASHEET
PARATHOM® SPECIAL T26

Special LED lamps for refrigerators



Areas of application

- Small designer luminaires
- Domestic refrigerators
- Sewing machines
- Outdoor applications only in suitable luminaires

Product benefits

- Extremely small dimensions
- Good all-around light emission
- Ideal for decorative and free-burning applications
- Long lifetime of up to 15,000 h
- Four year guarantee

Product features

- LED alternative to conventional high voltage lamps
- Good quality of light; color rendering index R_a: ≥ 80; constant chromaticity

© 2022, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Product description	Nominal wattage	Construction wattage	Nominal voltage	Claimed equiv. conventional lamp power	Nominal current
P SPC.T26 12 2.2 W/2700 K E14	2.2 W	2.20 W	220...240 V	12 W	14 mA
P SPC.T26 12 2.2 W/2700 K E14	2.2 W	2.20 W	220...240 V	12 W	14 mA
P SPC.T26 20 2.3 W/2700 K E14	2.3 W	2.30 W	220...240 V	20 W	18 mA
P SPC.T26 20 2.3 W/2700 K E14	2.3 W	2.30 W	220...240 V	20 W	24 mA
P SPC.T26 20 2.3 W/6500 K E14	2.3 W	2.30 W	220...240 V	20 W	18 mA
P SPC.T26 20 2.3 W/6500 K E14	2.3 W	2.30 W	220...240 V	20 W	24 mA
P SPC.T26 25 2.8 W/2700 K E14	2.8 W	2.80 W	220...240 V	25 W	24 mA
P SPC.T26 25 2.8 W/2700 K E14	2.8 W	2.80 W	220...240 V	25 W	17 mA
P SPC.T26 25 2.8 W/6500 K E14	2.8 W	2.80 W	220...240 V	25 W	17 mA
P SPC.T26 25 2.8 W/6500 K E14	2.8 W	2.80 W	220...240 V	25 W	24 mA
P SPC.T26 40 4 W/2700 K E14	4 W	4.00 W	220...240 V	40 W	35 mA
P SPC.T26 40 4 W/2700 K E14	4 W	4.00 W	220...240 V	40 W	35 mA

Product description	Type of current	Inrush current	Operating frequency	Mains frequency	Max. lamp no. on circuit break. 10 A (B)
P SPC.T26 12 2.2 W/2700 K E14	AC	0.185 A	50/60 Hz	50/60 Hz	270
P SPC.T26 12 2.2 W/2700 K E14	AC	0.03 A	50/60 Hz	50/60 Hz	267
P SPC.T26 20 2.3 W/2700 K E14	AC	4.6 A	50/60 Hz	50/60 Hz	30
P SPC.T26 20 2.3 W/2700 K E14	AC	3 A	50 Hz	50 Hz	42
P SPC.T26 20 2.3 W/6500 K E14	AC	4.7 A	50/60 Hz	50/60 Hz	38
P SPC.T26 20 2.3 W/6500 K E14	AC	3 A	50 Hz	50 Hz	42
P SPC.T26 25 2.8 W/2700 K E14	AC	6.81 A	50/60 Hz	50/60 Hz	80
P SPC.T26 25 2.8 W/2700 K E14	AC	0.23 A	50/60 Hz	50/60 Hz	230
P SPC.T26 25 2.8 W/6500 K E14	AC	0.23 A	50/60 Hz	50/60 Hz	230
P SPC.T26 25 2.8 W/6500 K E14	AC	6.81 A	50/60 Hz	50/60 Hz	80
P SPC.T26 40 4 W/2700 K E14	AC	7.08 A	50/60 Hz	50/60 Hz	60
P SPC.T26 40 4 W/2700 K E14	AC	0.2 A	50/60 Hz	50/60 Hz	115

Product description	Max. lamp no. on circuit break. 16 A (B)	Total harmonic distortion	Power factor λ
P SPC.T26 12 2.2 W/2700 K E14	430	< 125 %	0.65
P SPC.T26 12 2.2 W/2700 K E14	427	< 175 %	> 0.40
P SPC.T26 20 2.3 W/2700 K E14	38	< 175 %	> 0.40



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	Max. lamp no. on circuit break. 16 A (B)	Total harmonic distortion	Power factor λ
P SPC.T26 20 2.3 W/2700 K E14	67	< 80 %	> 0.40
P SPC.T26 20 2.3 W/6500 K E14	61	< 175 %	> 0.40
P SPC.T26 20 2.3 W/6500 K E14	67	< 80 %	> 0.40
P SPC.T26 25 2.8 W/2700 K E14	125	< 175 %	> 0.40
P SPC.T26 25 2.8 W/2700 K E14	370	< 125 %	0.65
P SPC.T26 25 2.8 W/6500 K E14	370	< 125 %	0.65
P SPC.T26 25 2.8 W/6500 K E14	125	< 175 %	> 0.40
P SPC.T26 40 4 W/2700 K E14	95	< 175 %	> 0.40
P SPC.T26 40 4 W/2700 K E14	230	< 175 %	0.50

Photometrical data

Product description	Luminous flux	Nominal useful luminous flux 90°	Luminous efficacy	Lumen main.fact.at end of nom.life time	Light color (designation)
P SPC.T26 12 2.2 W/2700 K E14	110 lm	110 lm	49 lm/W	0.90	Warm White
P SPC.T26 12 2.2 W/2700 K E14	110 lm	110 lm	49 lm/W	0.70	Warm White
P SPC.T26 20 2.3 W/2700 K E14	200 lm	200 lm	86 lm/W	0.70	Warm White
P SPC.T26 20 2.3 W/2700 K E14	200 lm	200 lm	86 lm/W	0.70	Warm White
P SPC.T26 20 2.3 W/6500 K E14	200 lm	200 lm	86 lm/W	0.70	Cool Daylight
P SPC.T26 20 2.3 W/6500 K E14	200 lm		86 lm/W	0.70	Cool Daylight
P SPC.T26 25 2.8 W/2700 K E14	250 lm	200 lm	89 lm/W	0.70	Warm White
P SPC.T26 25 2.8 W/2700 K E14	250 lm	250 lm	89 lm/W	0.90	Warm White
P SPC.T26 25 2.8 W/6500 K E14	250 lm	250 lm	89 lm/W	0.90	Cool Daylight
P SPC.T26 25 2.8 W/6500 K E14	250 lm	200 lm	89 lm/W	0.70	Cool Daylight
P SPC.T26 40 4 W/2700 K E14	470 lm	470 lm	117 lm/W	0.70	Warm White
P SPC.T26 40 4 W/2700 K E14	470 lm	470 lm	117 lm/W	0.90	Warm White

Product description	Color temperature	Color rendering index Ra	Light color	Standard deviation of color matching	Rated LLMF at 6,000 h
P SPC.T26 12 2.2 W/2700 K E14	2700 K	≥80	827	≤6 sdcm	0.80
P SPC.T26 12 2.2 W/2700 K E14	2700 K	80	827	≤6 sdcm	0.80
P SPC.T26 20 2.3 W/2700 K E14	2700 K	≥80	827	≤6 sdcm	0.80
P SPC.T26 20 2.3 W/2700 K E14	2700 K	≥80	827	≤6 sdcm	
P SPC.T26 20 2.3 W/6500 K E14	6500 K	≥80	865	≤6 sdcm	0.80
P SPC.T26 20 2.3 W/6500 K E14	6500 K	≥80	865	≤6 sdcm	
P SPC.T26 25 2.8 W/2700 K E14	2700 K	≥80	827	≤6 sdcm	0.80
P SPC.T26 25 2.8 W/2700 K E14	2700 K	≥80	827	≤6 sdcm	0.80



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	Color temperature	Color rendering index Ra	Light color	Standard deviation of color matching	Rated LLMF at 6,000 h
P SPC.T26 25 2.8 W/6500 K E14	6500 K	≥80	865	≤6 sdcm	0.80
P SPC.T26 25 2.8 W/6500 K E14	6500 K	≥80	865	≤6 sdcm	0.80
P SPC.T26 40 4 W/2700 K E14	2700 K	≥80	827	≤6 sdcm	0.80
P SPC.T26 40 4 W/2700 K E14	2700 K	≥80	827	≤6 sdcm	0.80

Product description	Flickering metric (Pst LM)	Stroboscope effect metric (SVM)
P SPC.T26 12 2.2 W/2700 K E14	0.1	0.1
P SPC.T26 12 2.2 W/2700 K E14		
P SPC.T26 20 2.3 W/2700 K E14	1.0	0.4
P SPC.T26 20 2.3 W/2700 K E14		
P SPC.T26 20 2.3 W/6500 K E14	1.0	0.4
P SPC.T26 20 2.3 W/6500 K E14		
P SPC.T26 25 2.8 W/2700 K E14		
P SPC.T26 25 2.8 W/2700 K E14	0.1	0.1
P SPC.T26 25 2.8 W/6500 K E14	0.1	0.1
P SPC.T26 25 2.8 W/6500 K E14		
P SPC.T26 40 4 W/2700 K E14		
P SPC.T26 40 4 W/2700 K E14	0.1	0.1

Light technical data

Product description	Beam angle	Warm-up time (60 %)	Starting time	Rated beam angle (half peak value)
P SPC.T26 12 2.2 W/2700 K E14	SPHERE_360	‹ 0.50 s	< 0.5 s	320.00 °
P SPC.T26 12 2.2 W/2700 K E14	320 °	‹ 0.50 s	< 0.5 s	320.00 °
P SPC.T26 20 2.3 W/2700 K E14	160 °	‹ 0.50 s	< 0.5 s	160.00 °
P SPC.T26 20 2.3 W/2700 K E14	160 °	‹ 0.50 s	< 0.5 s	160.00 °
P SPC.T26 20 2.3 W/6500 K E14	160 °	‹ 0.50 s	< 0.5 s	160.00 °
P SPC.T26 20 2.3 W/6500 K E14	160 °	‹ 0.50 s	< 0.5 s	160.00 °
P SPC.T26 25 2.8 W/2700 K E14	320 °	‹ 0.50 s	< 0.5 s	320.00 °
P SPC.T26 25 2.8 W/2700 K E14	320 °	‹ 0.50 s	< 0.5 s	320.00 °
P SPC.T26 25 2.8 W/6500 K E14	320 °	‹ 0.50 s	< 0.5 s	320.00 °
P SPC.T26 25 2.8 W/6500 K E14	320 °	‹ 0.50 s	< 0.5 s	320.00 °
P SPC.T26 40 4 W/2700 K E14	320 °	‹ 0.50 s	< 0.5 s	320.00 °
P SPC.T26 40 4 W/2700 K E14	320 °	‹ 0.50 s	< 0.5 s	320.00 °

Dimensions & Weight



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	Overall length	Diameter	Maximum diameter	Product weight
P SPC.T26 12 2.2 W/2700 K E14	63.00 mm	26.00 mm	26 mm	8.00 g
P SPC.T26 12 2.2 W/2700 K E14	63.00 mm	26.00 mm	26 mm	7.00 g
P SPC.T26 20 2.3 W/2700 K E14	63.00 mm	25.00 mm	25 mm	13.00 g
P SPC.T26 20 2.3 W/2700 K E14	63.00 mm	25.00 mm	25 mm	15.00 g
P SPC.T26 20 2.3 W/6500 K E14	63.00 mm	25.00 mm	25 mm	13.00 g
P SPC.T26 20 2.3 W/6500 K E14	63.00 mm	25.00 mm	25 mm	15.00 g
P SPC.T26 25 2.8 W/2700 K E14	63.00 mm	26.00 mm	26 mm	8.3 g
P SPC.T26 25 2.8 W/2700 K E14	63.00 mm	26.00 mm	26 mm	8.00 g
P SPC.T26 25 2.8 W/6500 K E14	63.00 mm	26.00 mm	26 mm	8.00 g
P SPC.T26 25 2.8 W/6500 K E14	63.00 mm	26.00 mm	26 mm	8.3 g
P SPC.T26 40 4 W/2700 K E14	80.00 mm	25.00 mm	25 mm	10.00 g
P SPC.T26 40 4 W/2700 K E14	80.00 mm	25.00 mm	25 mm	11.00 g

Temperatures & operating conditions

Product description	Ambient temperature range	Maximum temperature at tc test point
P SPC.T26 12 2.2 W/2700 K E14	-20…+40 °C	70 °C
P SPC.T26 12 2.2 W/2700 K E14	-20…+40 °C	65 °C
P SPC.T26 20 2.3 W/2700 K E14	-20…+40 °C	59 °C
P SPC.T26 20 2.3 W/2700 K E14	-20…+40 °C	80 °C
P SPC.T26 20 2.3 W/6500 K E14	-20…+40 °C	80 °C
P SPC.T26 20 2.3 W/6500 K E14	-20…+40 °C	80 °C
P SPC.T26 25 2.8 W/2700 K E14	-20…+40 °C	65 °C
P SPC.T26 25 2.8 W/2700 K E14	-20…+40 °C	70 °C
P SPC.T26 25 2.8 W/6500 K E14	-20…+40 °C	70 °C
P SPC.T26 25 2.8 W/6500 K E14	-20…+40 °C	65 °C
P SPC.T26 40 4 W/2700 K E14	-20…+40 °C	65 °C
P SPC.T26 40 4 W/2700 K E14	-20…+40 °C	70 °C

Lifespan

Product description	Nominal lamp life time	Number of switching cycles	Lumen maintenance at end of serv	Rated lamp survival factor at 6,000
P SPC.T26 12 2.2 W/2700 K E14	15000 h	100000	0.90	≥ 0.90
P SPC.T26 12 2.2 W/2700 K E14	15000 h	100000	0.70	≥ 0.90
P SPC.T26 20 2.3 W/2700 K E14	15000 h	100000	0.70	≥ 0.90
P SPC.T26 20 2.3 W/2700 K E14	15000 h	100000	0.70	≥ 0.90
P SPC.T26 20 2.3 W/6500 K E14	15000 h	100000	0.70	≥ 0.90



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	Nominal lamp life time	Number of switching cycles	Lumen maintenance at end of serv	Rated lamp survival factor at 6,000
P SPC.T26 20 2.3 W/6500 K E14	15000 h	100000	0.70	≥ 0.90
P SPC.T26 25 2.8 W/2700 K E14	10000 h	100000	0.70	≥ 0.90
P SPC.T26 25 2.8 W/2700 K E14	15000 h	100000	0.90	≥ 0.90
P SPC.T26 25 2.8 W/6500 K E14	15000 h	100000	0.90	≥ 0.90
P SPC.T26 25 2.8 W/6500 K E14	10000 h	100000	0.70	≥ 0.90
P SPC.T26 40 4 W/2700 K E14	15000 h	100000	0.70	≥ 0.90
P SPC.T26 40 4 W/2700 K E14	15000 h	100000	0.90	≥ 0.90

Additional product data

Product description	Base (standard designation)	Mercury content	Design / version
P SPC.T26 12 2.2 W/2700 K E14	E14	0.0 mg	Clear
P SPC.T26 12 2.2 W/2700 K E14	E14	0.0 mg	
P SPC.T26 20 2.3 W/2700 K E14	E14	0.0 mg	Frosted
P SPC.T26 20 2.3 W/2700 K E14	E14	0.0 mg	Frosted
P SPC.T26 20 2.3 W/6500 K E14	E14	0.0 mg	Frosted
P SPC.T26 20 2.3 W/6500 K E14	E14	0.0 mg	Frosted
P SPC.T26 25 2.8 W/2700 K E14	E14	0.0 mg	
P SPC.T26 25 2.8 W/2700 K E14	E14	0.0 mg	Clear
P SPC.T26 25 2.8 W/6500 K E14	E14	0.0 mg	Clear
P SPC.T26 25 2.8 W/6500 K E14	E14	0.0 mg	
P SPC.T26 40 4 W/2700 K E14	E14	0.0 mg	
P SPC.T26 40 4 W/2700 K E14	E14	0.0 mg	Clear

Capabilities

Product description	Dimmable
P SPC.T26 12 2.2 W/2700 K E14	No
P SPC.T26 12 2.2 W/2700 K E14	No
P SPC.T26 20 2.3 W/2700 K E14	No
P SPC.T26 20 2.3 W/2700 K E14	No
P SPC.T26 20 2.3 W/6500 K E14	No
P SPC.T26 20 2.3 W/6500 K E14	No
P SPC.T26 25 2.8 W/2700 K E14	No
P SPC.T26 25 2.8 W/2700 K E14	No
P SPC.T26 25 2.8 W/6500 K E14	No
P SPC.T26 25 2.8 W/6500 K E14	No



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	Dimmable
P SPC.T26 40 4 W/2700 K E14	No
P SPC.T26 40 4 W/2700 K E14	No

Certificates & Standards

Product description	Energy efficiency class	Energy consumption	Type of protection	Standards	Photobiological safety group acc. to EN62778
P SPC.T26 12 2.2 W/2700 K E14	G[1)]	3.00 kWh/1000h	IP20	CE / EAC	RG0
P SPC.T26 12 2.2 W/2700 K E14	G[2)]	3.00 kWh/1000h	IP20	CE / EAC / CB	RG0
P SPC.T26 20 2.3 W/2700 K E14	F[1)]	3.00 kWh/1000h	IP20	CE / EAC	RG1
P SPC.T26 20 2.3 W/2700 K E14	G[2)]	2.30 kWh/1000h	IP20	CE / EAC / CB	RG1
P SPC.T26 20 2.3 W/6500 K E14	F[1)]	3.00 kWh/1000h	IP20	CE / EAC	RG1
P SPC.T26 20 2.3 W/6500 K E14	G[2)]	2.30 kWh/1000h	IP20	CE / EAC / CB	RG1
P SPC.T26 25 2.8 W/2700 K E14	A++[2)]	3.00 kWh/1000h	IP20	CE / EAC / CB	RG0
P SPC.T26 25 2.8 W/2700 K E14	F[1)]	3.00 kWh/1000h	IP20	CE / EAC	RG0
P SPC.T26 25 2.8 W/6500 K E14	F[1)]	3.00 kWh/1000h	IP20	CE / EAC	RG0
P SPC.T26 25 2.8 W/6500 K E14	A++[2)]	3.00 kWh/1000h	IP20	CE / EAC / CB	RG0
P SPC.T26 40 4 W/2700 K E14	A++[2)]	4.00 kWh/1000h	IP20	CE / EAC / CB	RG0
P SPC.T26 40 4 W/2700 K E14	E[1)]	4.00 kWh/1000h	IP20	CE / EAC	RG0

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

2) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

LOGISTICAL DATA

Product description	Temperature range at storage
P SPC.T26 12 2.2 W/2700 K E14	-20...+80 °C
P SPC.T26 12 2.2 W/2700 K E14	
P SPC.T26 20 2.3 W/2700 K E14	-20...+80 °C
P SPC.T26 20 2.3 W/2700 K E14	
P SPC.T26 20 2.3 W/6500 K E14	-20...+80 °C



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	Temperature range at storage
P SPC.T26 20 2.3 W/6500 K E14	
P SPC.T26 25 2.8 W/2700 K E14	
P SPC.T26 25 2.8 W/2700 K E14	-20…+80 °C
P SPC.T26 25 2.8 W/6500 K E14	-20…+80 °C
P SPC.T26 25 2.8 W/6500 K E14	
P SPC.T26 40 4 W/2700 K E14	
P SPC.T26 40 4 W/2700 K E14	-20…+80 °C

Energy labellling regulation data acc EU 2019/2015

Product description	Lighting technology used	Non-directional or directional	Mains or non-mains	Light source cap-type (or other electric interface)	Connected light source (CLS)
P SPC.T26 12 2.2 W/2700 K E14	LED	NDLS	MLS	E14	No
P SPC.T26 12 2.2 W/2700 K E14				E14	
P SPC.T26 20 2.3 W/2700 K E14	LED	NDLS	MLS	E14	No
P SPC.T26 20 2.3 W/2700 K E14				E14	
P SPC.T26 20 2.3 W/6500 K E14	LED	NDLS	MLS	E14	No
P SPC.T26 20 2.3 W/6500 K E14				E14	
P SPC.T26 25 2.8 W/2700 K E14				E14	
P SPC.T26 25 2.8 W/2700 K E14	LED	NDLS	MLS	E14	No
P SPC.T26 25 2.8 W/6500 K E14	LED	NDLS	MLS	E14	No
P SPC.T26 25 2.8 W/6500 K E14				E14	
P SPC.T26 40 4 W/2700 K E14				E14	
P SPC.T26 40 4 W/2700 K E14	LED	NDLS	MLS	E14	No

Product description	Color-tuneable light source	Envelope	High luminance light source	Anti-glare shield	Correlated colour temperature type
P SPC.T26 12 2.2 W/2700 K E14	No	No	No	No	SINGLE_VALUE
P SPC.T26 12 2.2 W/2700 K E14					
P SPC.T26 20 2.3 W/2700 K E14	No	No	No	No	SINGLE_VALUE
P SPC.T26 20 2.3 W/2700 K E14					
P SPC.T26 20 2.3 W/6500 K E14	No	No	No	No	SINGLE_VALUE
P SPC.T26 20 2.3 W/6500 K E14					
P SPC.T26 25 2.8 W/2700 K E14					
P SPC.T26 25 2.8 W/2700 K E14	No	No	No	No	SINGLE_VALUE
P SPC.T26 25 2.8 W/6500 K E14	No	No	No	No	SINGLE_VALUE
P SPC.T26 25 2.8 W/6500 K E14					



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	Color-tuneable light source	Envelope	High luminance light source	Anti-glare shield	Correlated colour temperature type
P SPC.T26 40 4 W/2700 K E14					
P SPC.T26 40 4 W/2700 K E14	No	No	No	No	SINGLE_VALUE

Product description	Standby power	Claim of equivalent power	Length	Height	Width
P SPC.T26 12 2.2 W/2700 K E14	0.00	Yes	63.00 mm	26.00 mm	26.00 mm
P SPC.T26 12 2.2 W/2700 K E14			63.00 mm	26.00 mm	26.00 mm
P SPC.T26 20 2.3 W/2700 K E14	0.00	Yes	63.00 mm	25.00 mm	25.00 mm
P SPC.T26 20 2.3 W/2700 K E14			63.00 mm	25.00 mm	25.00 mm
P SPC.T26 20 2.3 W/6500 K E14	0.00	Yes	63.00 mm	25.00 mm	25.00 mm
P SPC.T26 20 2.3 W/6500 K E14			63.00 mm	25.00 mm	25.00 mm
P SPC.T26 25 2.8 W/2700 K E14			63.00 mm	26.00 mm	26.00 mm
P SPC.T26 25 2.8 W/2700 K E14	0.00	Yes	63.00 mm	26.00 mm	26.00 mm
P SPC.T26 25 2.8 W/6500 K E14	0.00	Yes	63.00 mm	26.00 mm	26.00 mm
P SPC.T26 25 2.8 W/6500 K E14			63.00 mm	26.00 mm	26.00 mm
P SPC.T26 40 4 W/2700 K E14			80.00 mm	25.00 mm	25.00 mm
P SPC.T26 40 4 W/2700 K E14	0.00	Yes	80.00 mm	25.00 mm	25.00 mm

Product description	Chromaticity coordinate x	Chromaticity coordinate y	Beam angle	Survival factor	LED light source replaces a fluorescent light source
P SPC.T26 12 2.2 W/2700 K E14	0.463	0.420	SPHERE_360	0.90	not applicable
P SPC.T26 12 2.2 W/2700 K E14					
P SPC.T26 20 2.3 W/2700 K E14	0.458	0.410	SPHERE_360	0.90	not applicable
P SPC.T26 20 2.3 W/2700 K E14					
P SPC.T26 20 2.3 W/6500 K E14	0.313	0.337	SPHERE_360	0.90	not applicable
P SPC.T26 20 2.3 W/6500 K E14					
P SPC.T26 25 2.8 W/2700 K E14					
P SPC.T26 25 2.8 W/2700 K E14	0.463	0.420	SPHERE_360	0.90	not applicable
P SPC.T26 25 2.8 W/6500 K E14	0.313	0.337	SPHERE_360	0.90	not applicable
P SPC.T26 25 2.8 W/6500 K E14					
P SPC.T26 40 4 W/2700 K E14					
P SPC.T26 40 4 W/2700 K E14	0.463	0.420	SPHERE_360	0.90	not applicable

Product description	EPREL ID	Model number
P SPC.T26 12 2.2 W/2700 K E14	522860	AC32149
P SPC.T26 12 2.2 W/2700 K E14		
P SPC.T26 20 2.3 W/2700 K E14	522880	AC32153



© 2022, LEDVANCE GmbH. All rights reserved.

Product description	EPREL ID	Model number
P SPC.T26 20 2.3 W/2700 K E14		
P SPC.T26 20 2.3 W/6500 K E14	522881	AC32154
P SPC.T26 20 2.3 W/6500 K E14		
P SPC.T26 25 2.8 W/2700 K E14		
P SPC.T26 25 2.8 W/2700 K E14	522861	AC32150
P SPC.T26 25 2.8 W/6500 K E14	522862	AC32151
P SPC.T26 25 2.8 W/6500 K E14		
P SPC.T26 40 4 W/2700 K E14		
P SPC.T26 40 4 W/2700 K E14	522863	AC32152

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

SALES AND TECHNICAL SUPPORT

Sales and Technical Support www.ledvance.com

COUNTRY SPECIFIC INFORMATION

Product description	Product code	METEL-Code	SEG number	STK number	UK Org
P SPC.T26 12 2.2 W/2700 K E14	4058075616912	-	8296944	-	-
P SPC.T26 12 2.2 W/2700 K E14	4058075432215	-	8295507	4731557	-
P SPC.T26 20 2.3 W/2700 K E14	4058075620254	-	8296942	-	-
P SPC.T26 20 2.3 W/2700 K E14	4052899961289	-	8296000	4730514	-
P SPC.T26 20 2.3 W/6500 K E14	4058075620155	-	8296943	-	-
P SPC.T26 20 2.3 W/6500 K E14	4052899961302	-	8295999	4739115	-
P SPC.T26 25 2.8 W/2700 K E14	4058075133471	-	8294159	-	-
P SPC.T26 25 2.8 W/2700 K E14	4058075616875	-	8296945	-	-
P SPC.T26 25 2.8 W/6500 K E14	4058075616837	-	8296946	-	-
P SPC.T26 25 2.8 W/6500 K E14	4058075133426	-	8294160	-	-
P SPC.T26 40 4 W/2700 K E14	4058075133525	-	8294161	-	-
P SPC.T26 40 4 W/2700 K E14	4058075616790	-	8296947	-	-

DOWNLOAD DATA



© 2022, LEDVANCE GmbH. All rights reserved.

	DOWNLOAD DATA
PDF	Declarations of conformity LED lamp T26 FIL
PDF	Declarations of conformity LED SLIM LINE 78 60 NON-DIM
PDF	PRODUCT DATASHEET P SPC.T26 20 2.3 W 2700K E14 DATASHEET
PDF	Declarations of conformity LED SLIM LINE 78 60 NON-DIM
PDF	PRODUCT DATASHEET P SPC.T26 20 2.3 W 6500K E14 DATASHEET
PDF	PRODUCT DATASHEET P SPC.T26 25 2.8 W 2700K E14 DATASHEET
PDF	Declarations of conformity EC declaration T26 25 FIL, T26 40 FIL
PDF	Declarations of conformity LED lamp T26 FIL
PDF	Declarations of conformity LED lamp T26 FIL
PDF	PRODUCT DATASHEET P SPC.T26 25 2.8 W 6500K E14 DATASHEET
PDF	Declarations of conformity EC declaration T26 25 FIL, T26 40 FIL
PDF	PRODUCT DATASHEET P SPC.T26 40 4 W 2700K E14 DATASHEET
PDF	Declarations of conformity EC declaration T26 25 FIL, T26 40 FIL
PDF	Declarations of conformity LED lamp T26 FIL

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075616912	Folding box 1	28 mm x 28 mm x 67 mm	13.00 g	0.05 dm^3
4058075432215	Folding box 1	28 mm x 28 mm x 67 mm	12.00 g	0.05 dm^3
4058075620254	Folding box 1	28 mm x 28 mm x 67 mm	18.00 g	0.05 dm^3



© 2022, LEDVANCE GmbH. All rights reserved.

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899961289	Folding box 1	28 mm x 28 mm x 67 mm	20.00 g	0.05 dm^3
4058075620155	Folding box 1	28 mm x 28 mm x 67 mm	18.00 g	0.05 dm^3
4052899961302	Folding box 1	28 mm x 28 mm x 67 mm	20.00 g	0.05 dm^3
4058075133471	Folding box 1	28 mm x 28 mm x 67 mm	13.00 g	0.05 dm^3
4058075616875	Folding box 1	28 mm x 28 mm x 67 mm	13.00 g	0.05 dm^3
4058075616837	Folding box 1	28 mm x 28 mm x 67 mm	13.00 g	0.05 dm^3
4058075133426	Folding box 1	28 mm x 28 mm x 67 mm	13.00 g	0.05 dm^3
4058075133525	Folding box 1	28 mm x 28 mm x 84 mm	14.00 g	0.07 dm^3
4058075616790	Folding box 1	28 mm x 28 mm x 84 mm	15.00 g	0.07 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



© 2022, LEDVANCE GmbH. All rights reserved.