PHILIPS

Lighting



Xitanium LED downlight and spotlight drivers

Xitanium 23W/m 0.5A 46V SC 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information	
Lighting Technology	LED

Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	500 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	23 W
Output Power (Min)	15.5 W
Output Current (Min)	500 mA
Output Voltage (Max)	46 V
Output Voltage (Min)	31 V

System characteristics	
Central DC Operation	No
YellowDot ready	No

Temperature	
T-Case Lifetime (Max)	75 °C
T-Case Maximum (Max)	75 °C

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Product Length	97 mm
Housing	Mini 97x43x30 2p2p
Overall length	97.2 mm
Overall width	43 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 43 x 97 mm

Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance
Output Current Set Options	Preset Current
Protection class IEC	Safety class I/II

Product Data	
Order product name	Xitanium 23W/m 0.5A 46V SC 230V

Xitanium LED downlight and spotlight drivers

Full product name	Xitanium 23W/m 0.5A 46V SC 230V
Full product code	871869970219900
Order code	70219900
Material Nr. (12NC)	929002104906
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.064 kg

EAN/UPC - Product/Case	8718699702199
Numerator - Packs per outer box	50
EAN/UPC - Case	8718699702205

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.